



COMPARATIVE STSTEMENT OF PRICE BID OF FURNITURE'S ITEMS RECEIVED AGAINST TENDER NOTICE NO.19/2022-23/Furniture/IGIMS/Store

. NO Name of the Items	M/s. Ansh Enterprises, Road No-8, North Patel nagar, P O - Keshri Nagar, Patel Nagar, Patna-800024	M/s Jaymanti Tara Infra Service, Pvt. Ltd., Harimandir Gali Ward No- 66, Patna City-800008	M/s. Prakash Enterprises, Danapur Cantt., Patna	M/s. Unik Surgical Pvt. Ltd., House N0-2-C/159, G D Mishra Path, New Patliputra, Patna	M/s. Seema Steel Products, Ambedkar Chowk, Danka Imli, Opp. Gandhi Setu Gai Ghat, Patna-800007	M/s. Excel Industries, Ambedkar Chowk, Danka Imli, Opp Gandhi Setu, Gai Ghat, Alamganj, Patna-800007	M/s. Hosco Private Limited, 111, Chittaranjan Avenue, Kolkata-700073	M/s Vaishali Industrial Products, B-2, Phase-II, Industrial Area, Hajipur, Vaishali-844102	M/s. Asha Homes Infra Pvt. Ltd, S.S Square Apartment, Ashokpuri, Aashiyana Road, Pana-800014	Remarks
Over Bed Trolley Rectangular Frame work mounted on 5 cm castors. Two section wooden top. Height adjustable by gear on stainless steel frame. Base frame Pre treated and epoxy powder coated. Size: L. 810 x W 380 x H 750-1050 mm.	Not Accepted	₹4,484.00	₹4,248.00	Not Accepted	₹7,080.00	₹8,496.00	Not Accepted	₹8,850.00	Not Accepted	M/s. Prakash Enterprises, Danapur Cantt., Patna ₹4,248.00 Found L1
2 INSTRUMENT TROLLEY • Overall size: Size: 680mm L x 450mm W x 900mm H. Stainless steel tubular frame work made of 25 4mm OD x 18 G verticals mounted on 100 mm dia non-rustlings wiveling castor wheels two with brakes, two without brakes. Two stainless steel shelves with protective railings on three sides. Only 304 grade stainless steel should be used for trolley frame work and STAINLESS STEEL shelves.	₹10,502.00	₹9,322.00	Not Accepted	₹8,150.00	Not Accepted	₹10,856.00	₹9,864.80	₹9,204.00	₹25,160.00	M/s. Unik Surgical, Patna ₹8,150.00 Found L1
3 CRASH CART • Size 960mm L x 500mm W x 1545mm H. Frame work		₹16,662.78	Not Accepted	₹16,166.00	₹21,830.00	₹18,880.00	₹23,128.00	₹25,998.00	Not Submitted	M/s. Unik Surgical, Patna

chinimum 25mm dia Two ght weight polystyrene boxes each with three drawers, upper drawer with medicine container of different sizes Provision to hold Oxygen cylinder and cardiac Massage Board Six numbers colored hand out bins to keep important supplies at eye level Two nos Stainless Steel shelves to carry monitors, ECG Machine, suction apparatus etc Provided with corner										₹16,166.00 Found L1
buffers & Rails All stainless steel components should be of 304 quality Crash cart should be movable on four non-rusting swivel casters of 125mm dia two with brake. DRESSING TROLLEY Overall Size: 1010 mm L x 510 mm W x 900mm H	₹11,916.82	₹9,322.00	Not Submitted	₹7,500.00	₹9,440.00	Not Accepted	₹11,497.92	₹11,682.00	Not Submitted	M/s. Unik Surgical, Patna
welded stainless steel tubular frame work. • Verticals of also 31.7mm OD x 18 G tube horizontal stays of 19 mm OD x 18 G tube on all four sides to support two stainless steel shelves 22 G over with 10 mm dia stainless steel railings are provided on all four sides. • The trolley holds stainless steel bucket with STAINLESS STEEL lid at lower.										₹7,500.00 Found L1
level respectively. Only 304 grade stainless steel should be used for tubular frame work & STAINLESS STEEL shelves of trolley. The trolley should be in building the standard		Jananara .	67.00°2	July 7.072 Page 2	of 12 Janos	E STOTI	3 alm	(77)	Vanstale 04/04/2023	, i

	without brakes.						•				
5	Medicine Trolley Two sides unit cassette and one side plate cassette Installed multi-bin container at rear side to make easy and multi-storing possible Multi structure, which can be used for multi proposes. Designed push-handle and efficient structure Total lock key compartment under the surface.	₹14,866.82	₹9,558.00	Not Submitted	Not Accepted	₹11,210.00	Not Accepted	₹15,917.02	₹18,900.00	₹45,220.00	M/s. Jaymanti Tara Infra, Patna ₹9,558.00 Found L1
	Size: 778 (L) x 488 (D) x 918 (H) minimum 781 (L) x 491 (D) x 921 (H) maximum										
6	SS REVOLVING STOOL Overall Size: 480mm To 670mm H. Tubular tripod base of 25.4 x 14 g ERW tube. STAINLESS STEEL top. Height adjustment by screw. 300mm dia The legs fitted with high quality PVC shoes with nylon reinforcement. All mild steel components should be thoroughly inhouse pretreated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing, pickling, phosphating each	₹1,886.82	₹3,068.00	Not Accepted	Not Accepted	₹2,596.00	₹2,336.40	₹3,964.80	₹3,894.00	₹4,845.00	M/s. Ansh Enterprises, Patna ₹1,886.82 Found L1
	followed by water rinsing passivating and hot air drying to give phosphate		, John St.	Cornois)	Page 3 (of 12	E STITIO	aAlm	- B	Vamtob	ls.
	OXL/	6	/	7	, , ,		לוייןיט	7 0 1	-	- 1	٦

										T	T
	coating. The treated metal surface should then be coated inhouse with epoxy polyester powder with paint film thickness of 60 microns (minimum) and oven baked at 180 deg to 200 deg. centigrade. All STAINLESS STEEL used should be of 304 grade.										
7	BED SIDE STOOL/All	₹824.82	₹1,298.00	Not Submitetd	₹600.00	₹1,593.00	₹1,003.00	₹2,065.00	Not Accepted	Not Submitetd	M/s. Unik
	Purpose Stool							1 7 1 1 3			Surgical,
. !	Size: 300mm square 18G		l .							1	
	1 11 1 1 1 1 1 1 1 1 1									1	Patna
	double bent top of MS,							- 4			Patna
	double bent top of MS, Height 510mm. Framework							- 4 - 1			Patna
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and							- 4			Patna ₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm							- 4 - 1			
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube										₹600.00
	double bent top of MS, Height 510mm Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps.										
	double bent top of MS, Height 510mm Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil,										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes,										₹600.00
	double bent top of MS, Height 510mm Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing.										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing pickling, phosphating each										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing pickling, phosphating each followed by Waterrinising										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing, pickling, phosphating each followed by Waterrinising passivating and hot air										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing pickling, phosphating each followed by Waterrinising										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing pickling, phosphating each followed by Waterrinising passivating and hot air drying to give phosphate coating. • The treated metal surface										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing pickling, phosphating each followed by Waterrinising passivating and hot air drying to give phosphate coating. • The treated metal surface should then be coated in-										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing pickling, phosphating each followed by Waterrinising passivating and hot air drying to give phosphate coating. • The treated metal surface should then be coated inhouse with epoxy polyester										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing, pickling, phosphating each followed by Waterrinising passivating and hot air drying to give phosphate coating. • The treated metal surface should then be coated inhouse with epoxy polyester Powder with paint film										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing pickling, phosphating each followed by Waterrinising passivating and hot air drying to give phosphate coating. • The treated metal surface should then be coated inhouse with epoxy polyester Powder with paint film thickness of 60 microns										₹600.00
	double bent top of MS, Height 510mm. Framework of 25mmx 1.22 mm and horizontal support of 19 mm x 1.22 mm CRC Tube • Leg fitted with PVC Stumps. All mild steel components should be thoroughly inhouse pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degrasing, pickling, phosphating each followed by Waterrinising passivating and hot air drying to give phosphate coating. • The treated metal surface should then be coated inhouse with epoxy polyester Powder with paint film										₹600.00

Page 4 of 12 Page 4 of 12 Page 7/7/27 RAMIN STORY PAGE 4 of 12 Page 4

,	A			•			•				
8	Steel Rack Steel Rack - Gauge: 20 Stee (in mm) 915X381X2438 No. of shelves 5 Weight carriage 100 kgs	Not Accepted	83,850.00	Not Submitetd	Not Accepted	Not Accepted	Not Accepted	₹10,110.24	₹7,000.00	₹15,000.00	M/s. Vaishali Industrial, Hajipur ₹7,000.00 Found L1
9	Emergency & Recovery	Not Accepted	Not Accepted	Not Submitted	Not Accepted	₹53,100.00	Not Accepted	₹41,300.00	₹39,530.00	Not Submitetd	M/s. Vaishali Industrial,
	Sizes should be approx.2100mm x 650mm x 650 – 950mm Should be attached with side railing, IV Stand, Storage Tray & Cylinder Cage.										Hajipur ₹39,530.00 Found L1
	Should have removable x-ray translucent top with tray for holding x-ray cassettes. Should have adjustable height facility through hydraulic system. Should have the facility of trendlenburg & reverse trendlenburg by pressure cylinder.					-					
	Suitable castors with two brakes & rubber buffer on all corners should be available. Should be pre treated and epoxy powder coated										

Page 5 of 12 Plants OT/07/ 67 07:23 Postorhous

,							Sid hamid	Not Submitted	₹12,200.00	₹22,100.00	M/s. Vaishali
10	Book Self. • Full Size Book Shelves, 4 Shelves Book Self, Premium Quality.	Not Accepted	Not Submitted	Not Sbmitted	Not Accepted	Not Submitted	Not Accepted				Industrial, Hajipur ₹12,200.00 Found L1
11	Steel Rack: • Size-06"x36"x15" with six shelves with spray painting GCR sheet.	Not Accepted	Not Submitted	Not Submitted	Not Accepted	Not Submitted	Not Accepted	₹7,103.60	₹7,000.00	Not Submitetd	M/s. Vaishali Industrial, Hajipur ₹7,000.00 Found L1
12	STEEL ALMIRAH • General Requirement	Not Accepted	Not Accepted	Not Submitted	₹10,000.00	Not Submitted	Not Accepted	Not Accepted	₹17,000.00	₹25,712.00	M/s. Unik Surgical, Patna
	Technical specification of Almirah steel-Generally conforming to BIS specification IS: 3312:2021 (with latest amendment) Type of Almirah steel-Almirah Steel shelving cabinets Construction type-Welded Installation-Free standing Pedestal-Yes										₹10,000.00 Found L1
	Pedestal fitted with-3 mm Teflon Bush Pedestal height (± 5 mm)- 125 mm Locker required-Yes Door type-Hinged Number of door-2 Number of hinges (for each		<i>"</i> "								

(A)

Sparity (

of stroig

Page 6 of 12

07/07/2

Ahm 07-13

OHOHDOS

door)-2			-			(C)			
Door stiffener	up to full			•		•			
door height pro	vided-Yes								
 Number of shell 	lves-4								
 Uniformly distr 	ributed load								
(UDL) for shelv	ves-80 kgs.								
Wardrobe by st									
 Colour of 	finish-Silver								
Grey									
Material									
Steel sheet mat	terial-CRCA								
sheets conform									
CRI of IS 513() (with latest ame									
Sheet rounds									
Conforming to									
of 1S 2062	grade 1230							1	
Screws-Conform	mine to IS								
1365									
Hanging rod	material-								
Aluminium Tub									
Mirror frame n									
(if provided)-									
frame									
Tie hanger ma	ade out of-								
N.A									
	material-No								
stiffener					,				
 Dimension 			1						
 Almirah heigh 									
the height of pe	edestal) ± 5								
mm-1950 mm									
Almirah width :	± 5 mm-4 /0								
mm	. 5 202								
Almirah depth = mm	± 5 mm-302								
Locker inside	height + 5								
mm-No locker	ikigin ± 3								
Side sheet the	hickness-0.9								
mm									
Back sheet th	hickness-0.8							1	
mm								1	
Top sheet th	hickness-0.8								
mm								1	
Bottom sheet the shee	hickness-0.8								
mm									
 Shelves sheet th 	hickness-0.6		1:						
mm						les vers e a l			
Shelves support		1 4							
thickness-1.6 m									
Door metal									
thickness-0.8 m									
Pedestal sheet	thickness-								
0.8 mm	historica 16								1
Hinges sheet themm	nickness-1.6	23.	1 2						
1 11111					-				

	Stiffener sheet thickness- 0.6 mm Håndle size-15 cm LOCKS AND LOCKING ARRANGEMENT Steel Almirah lock/locker lock-Six lever lock Material of lock-MAZAK Zinc plated Duplicate keys (for each lock)-Keys made of MAZAK/ZAMAK having nickel plated finish Keys made of MAZAK/ZAMAK having nickel plated finish-A three way bolting device controlled by a lock Door handle material for almirah lock-Stainless steel FINISH All the mild steel parts shall be given phosphating treatment-Conforming to Class c of IS 3618 Finish coat with enamels- Stoving enamel										
13	BED SIDE LOCKER Overall Size (Approx): 40 (H) x 40 (W) x 80 (H) cms. Should have an enclosed locker unit which is provided with 50 mm dia non rusting castors for mobility A stainless Steel tray top with raised borders on 3 sides forming the upper surface. Drawer should be fitted with smooth slides. Should be provided with self space for		Not Accepted	Not Submitted	₹3,200.00	₹5,192.00	₹4,543.00	Not Accepted	₹5,782.00	₹8,288.00	M/s. Unik Surgical, Patna ₹3,200.00 Found L1
	Ship sheet in	, Jews	A CONTRACTOR OF THE PROPERTY O	was fr	Page 8	B of 12	, OT[07]	3	2Ahr 07-07-2	3 Cathorhouse	8 130

Scanned with CamScanner

									•		
	Storage under the Drawer with locked Calmet at below Drawer and cabinet should have front			•			•				
	door. • Should have one drawer & one cabinet box with self space in between.										
	The body should be made of 20 G MS CRCA sheet. All MS parts to be pre- treated and epoxy powder coated.										
	• All SS to be of 304 Grade and of 16 Gauge. Warranty: 3year CIDEX TRAY	₹8,732.00	Not Submitted	Not Submitted	Not Submitted	Not Submitted	₹7,670.00	₹2,273.60	₹5,310.00	Not Submitetd	M/s. Hosco
'	Cidex Tray with SS Cover. Size (in mm): 650 x 180 x 110 (Approx.)	(8,732.00	Not Submitted	Not Submitted	Not Submitted	AGC Submitted	(1,070.00				Private, Kolkata
	Made up of 20G Stainless steel Warranty: 1year							F17 047 50	₹11,564.00	₹1,01,405.00	Found L1 M/s. Vaishali
5	FOWLERS BED Semi fowlers' bed made of Rectangular M.S Tube with two sections Top The top should be made of CRCA perforated sheet. Back rest section has to be maneuvered by screw handle at foot end up to an Angle	Not Accepted	Not Accepted	Not Accepted	Not Accepted	Not Accepted	Not Accepted	₹17,847.50	C11,504.00	(1,01,405.00	Industrial, Hajipur ₹11,564.00 Found L1
	of 60degree S S laminated Head and Foot boards Location of one IV Rod should be available. Bed should be mounted on										
	100mm dia caster. Two section mattress with 3" thick PU foam of 40 density covered with PVC Rexine Approximate Dimension 2001.x90										27
	wx 60H (in cms) Finish should be Pre treated & Epoxy powder coated Warranty: 3year							*** *** ***		* * * * * *	
-		Not Submitted	Not Submitted	Not Submitted	Not Accepted	Not Submitted	Not Accepted	Not Submitted	Not Submitted	Not Submitetd	
16		Not Submitted	Not Submitted	110t Bubilitted							_
	Overall approximate										_
	dimension: 950 mm x 500		h.								

mm x 1500 mm (L x W x

Page 9 of 12

	Stainless steel tubular frame & S.S. Shelves. Six removable bins and two polystyrene lockable storage units with three drawers having containers of different sizes. Four 100mm diameter Castors with high grade synthetic body. Warranty: 3 year						•				
17	3 Seater Bench made of Steel (Airport Chair) • Each set containing 3 Seats. • Approx. overall dimension. 160 (L) x 45 (D) x 77 (H) cm. • Material. cold rolled steel. • Seat Board. Cold. Rolled Perforated. Steel. Board. of 18 Swg. Or better Colour / Funish. Epoxy Powder. Coated in Chromium Silver gray or black colour.	₹10,031.18	Not Accepted	Not Submitted	Not Accepted	Not Accepted	Not Accepted	Not Submitted	Not Accepted	Not Submitetd	Single Quoted
18		Not Submitted	Not Submitted	Not Submitted	₹14,500.00	Not Submitted	Not Accepted	Not Submitted	₹37,496.00	₹58,225.00	M/s. Unik Surgical, Patna ₹14,500.00 Found L1
	and Backrest-Moulded plywood of 12±1mm thickness Material of Seat cover- recin Material of Seat-foam with	~1	S.								

Total Page 10 of 12

- 1	Material of Side Frame-SS										
	304 Round pipeDiameter										
. [25 Mm x 1.6 Mm Thick										
	Material used for										
	connecting tie member and										
	side frames-injected										
	moulded black ABS and										
	black oxidized socket head										
	screws with nuts made of									1	
	MS bright bars of diameter										
	15.8 mm with 8 mm BSW										
	threads										
	Density of foam for										1
	backrest ±5 (Kg/Cub M)-										1
	32									1	
	 Density of foam for seat ±5 									1	
	(Kg/Cub M)-32										
	Material of Backrest-foam										
	with 25 percent										
	compression										
	Cover of Foam on armrest-							-			
	rexin										
	Compression of foam-25										
	percent							100			
	Thickness of Foam on						4				
	armrest ±2 (mm)-45						11 24	The latest			
	GSM of seat, backrest and						*: 16				
	armrest cover (GSM) ±5%-										
	150										
	Shoes-rubber shoes						1				
	Material of Tie member-						3				
	MS ERW Tube Of										
	Diameter 31.8 Mm x 2 Mm										
	Thick										
	Dimension										
	• Seat Thickness ±2 (mm)-75										
- 1	• Seat Depth ±5(mm)-560										
	• Seat Width ±5 (mm)-520										
	Backrest Thickness ±2										
	(mm)-75										
	Backrest Width ±5 (mm)-										
	520										
	Backrest Height ±5 (mm)-		2 2 2 8 4 1 F (6) 6 1				7 L S *				
	355										
	• Arm Depth ± 5(mm)-460										Pi a
	• Arm width ±2 (mm)-150										
	• Arm Height ±3 (mm)-280		L.								4-
	• Finish		7 7.								95
	Chrome Plated	1000 30							`		
		September 1		/	Page 11	of 12					
	A	\$\times_{\time	Carear or		~~~~ 1 age 11	of 12			RAhr		
	©ks⁄o ≪	'm M	6/20	hus a	.07	W	110.		KANNE	22 kanstale	_
	-3111		1200	1300		100	ツリ <i>ツ</i>		12-07	alvabo	3 F.
			10	-		יןיט ־			- 07	COHOLI	2 12
						•					•

Scanned with CamScanner

									1	
• WARANTEE PERIOD IN NUMBER OF YEARS-I							No Submitted	₹22,302.00	₹48,280.00	M/s. Vaishali
Examination Couch Size: 72 L x 24 W x 32 H Inch Finish Type: Pretreated & epoxy powder coated Foldable: Yes Load Capacity: 90 to 140 kg Storage: Three Drawers & three Cabinet	Not Submitted	Not Accepted	Not Submitted	Not Submitted	Not Accepted	₹28,910.00	Not Submitted	(22,302.00	(45,250.50	Industrial, Hajipur ₹22,302.00
BP Holder Attached IV Pole Attached Footstool Attached Table made of 20g CR Sheet, 12mm plywood with 3 foam on top covered by rexine cloth, Screwed with a table.						* *				

044V

Ozto zrinacia.

207.003

Jun 7.07.27

James 7/2/23

07/07/2

24mm

Carport 1003.